


WAAS CH 40308 W16A	APP CRS 156°	Rwy Ldg TDZE 686 Apt Elev 686
--	------------------------	---

RNAV (GPS) RWY 16
HILLSBORO MUNI (INJ)



Baro-VNAV NA when using Cleburne Rgnl altimeter setting. DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Visibility reduction by helicopters NA. When local altimeter setting not received use Cleburne Rgnl altimeter setting and increase all DA/MDA 80 feet, increase LPV and LNAV/VNAV visibility 1/4 mile all Cats.

MISSED APPROACH: Climb to 3000 direct ILUCU and hold.

AWOS-3PT 118.725	WACO APP CON ★ 127.65 352.0	CTAF 122.90
----------------------------	---------------------------------------	-----------------------



ELEV 686	TDZE 686
-----------------	-----------------



CATEGORY	A	B	C	D
LPV DA	936-1	250 (300-1)		NA
LNAV/VNAV DA	1128-1½	442 (500-1½)		NA
LNAV MDA	1120-1	434 (500-1)		NA
CIRCLING	1180-1 494 (500-1)	1200-1 514 (600-1)		NA

SC-2, 19 FEB 2026 to 19 MAR 2026

SC-2, 19 FEB 2026 to 19 MAR 2026