


WAAS CH 99311 W12A	APP CRS 123°	Rwy Ldg 4000 TDZE 42 Apt Elev 42
--	------------------------	---

RNAV (GPS) RWY 12
QUINHAGAK (AQH) (PAQH)

RNP APCH.	Procedure NA at night. Baro-VNAV and VDP NA when using Kipnuk altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. When local altimeter setting not received, use Kipnuk altimeter setting and increase all DA and MDA 160 feet; increase LPV all Cats visibility and LNAV/VNAV all Cats visibility $\frac{1}{8}$ SM, LNAV Cats C, D visibility $\frac{3}{8}$ SM, increase Circling Cat C visibility $\frac{1}{2}$ SM, increase Circling Cat D visibility $\frac{1}{4}$ SM.	MISSED APPROACH: Climb to 5200 direct CUTEB and hold, continue climb-in-hold to 5200.
-----------	---	---

AWOS-3P 121.575	ANCHORAGE CENTER 125.2 372.0	KENAI RADIO 122.1	UNICOM 122.8 (CTAF) 0
---------------------------	--	-----------------------------	---------------------------------



4 NM Holding Pattern		HOTKU		JOSAD		5200 ↑		CUTEB ✦	
6000 ← 303° 2500 → 123°				123° 1600		*LNAV only.			
GP 3.00° TCH 35				1600		*1.4 NM to RW12		RW12	
		5.9 NM		3.4 NM		1.4 NM			
CATEGORY	A	B	C	D					
LPV DA	292-1 250 (300-1)								
LNAV/VNAV DA	292-1 250 (300-1)								
LNAV MDA	500-1	458 (500-1)	500-1 $\frac{3}{8}$	458 (500-1 $\frac{3}{8}$)					
CIRCLING	500-1	458 (500-1)	580-1 $\frac{1}{2}$ 538 (600-1 $\frac{1}{2}$)	600-2 558 (600-2)					

ELEV 42	TDZE 42
MIRL Rwy 12-30 0	

AK, 22 JAN 2026 to 19 MAR 2026

AK, 22 JAN 2026 to 19 MAR 2026