


WAAS CH 56535 W30A	APP CRS 301°	Rwy Ldg TDZE 129 Apt Elev 166
--	------------------------	---

RNAV (GPS) RWY 30


ROY WILCOX (5R1)

NA DME/DME RNP-0.3 NA. Procedure NA at night. Rwy 30 helicopter visibility reduction below 1 SM NA. Use Mobile Rgnl altimeter setting; when not received, use Hattiesburg Bobby L Chain Muni altimeter setting and increase all MDA 20 feet; increase LNAV Cat C visibility ½ SM.	MISSED APPROACH: Climb to 2000 direct JOVOK and hold.
---	--

MOB ASOS 124.75 257.85	HOUSTON CENTER 127.65 285.475	UNICOM 122.8 (CTAF)
----------------------------------	---	-------------------------------



ELEV 166	TDZE 129
----------	----------



2000	JOVOK	Visual Segment - Obstacles.	WIPAR	4 NM Holding Pattern
↑	✧			
		YOSLU 2.2 NM to RW30	ZEDEG 1800	WIPAR 2000
		RW30		
		2.2 NM	2.9 NM	5 NM
CATEGORY	A	B	C	D
LP MDA	680-1	551 (600-1)	680-1½ 551 (600-1½)	NA
LNAV MDA	700-1	571 (600-1)	700-1½ 571 (600-1½)	NA
CIRCLING	740-1 574 (600-1)	760-1 594 (600-1)	940-2¼ 774 (800-2¼)	NA