

WAAS CH 50347 W35A	APP CRS 347°	Rwy Ldg TDZE Apt Elev	3500 1308 1309
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35






REDFIELD MUNI (1D8)

RNP APCH - GPS.

⚠ Baro-VNAV and VDP NA when using ABR altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter not received, use ABR altimeter setting and increase LPV DA to 1694 feet and all visibilities 1/8 SM. Increase LNAV/VNAV DA to 1844 feet and all visibilities 1/8 SM. Increase all MDAs 100 feet.

MISSED APPROACH: Climb to 3400 direct BOTJO and hold.

AWOS-3P 118.525	MINNEAPOLIS CENTER 126.25 339.8	UNICOM 122.8 (CTAF) 0
---------------------------	---	---------------------------------



CATEGORY	A	B	C	D
LPV DA	1558-1	250 (300-1)		NA
LNAV/VNAV DA	1760-1 3/8	452 (500-1 3/8)		NA
LNAV MDA	1800-1	492 (500-1)		NA
CIRCLING	1820-1 511 (600-1)	1900-1 591 (600-1)		NA

NC-1, 19 FEB 2026 to 19 MAR 2026

NC-1, 19 FEB 2026 to 19 MAR 2026