| LOC/DME I-JKI | APP CRS | Rwy Ldg | 10000 |
|---|---|---|---|
| 111.95 | 216° | TDZE | 642 |
| Chan 56 (Y) | | Apt Elev | 645 |

# ILS PRM Z RWY 22R (CLOSE PARALLEL)

## DETROIT METRO WAYNE COUNTY (DTW)

RNAV 1-GPS. HRRON and VALLI: RNAV 1-DME/DME/IRU or GPS required.
Aircraft not DME/DME/IRU or GPS equipped - RADAR required for procedure entry.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF Comm required. See additional requirements on AAUP.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1100 then climbing right turn to 4000 on DXO VOR/DME R-297 to DOHNT INT/DXO 15.5 DME/RADAR and hold.

| D-ATIS | DETROIT APP CON | METRO TOWER | GND CON | CLNC DEL | CPDLC |
|---|---|---|---|---|---|
| 133.675 | 124.05 284.0 | 135.0 317.725 PRM 127.05 | 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE) | 120.65 | |

ALTERNATE MISSED APCH FIX
DOHNT
090°
270°
4 NM

MSA DXO 25 NM
2800

(IAF) HRRON 6000 210K
4000 113° (6.9)
PRYDE 4000
4000 to FUDDJ 190° (5.7)
KLIER 4000
4000 097° (7.6)
(IAF) VALLI 6000 210K
4000 to FUDDJ 173° (4)
(IAF) INKSR I-JKI 20 RADAR
036°
4000 216° (1.4)
FUDDJ I-JKI 18.7 RADAR
TARAH I-JKI 16.5 RADAR
1750
4000 216° (2.1)
GUYVE I-JKI 13.4 RADAR
JOYDD I-JKI 10.2 RADAR
(IF) NUJNT I-JKI 7.1 RADAR
SALEM 114.3 SVM Chan 90
DOHNT INT DXO 15.5 RADAR
R-218
117°
297°
DETROIT 113.4 DXO Chan 81
R-297
GEETR I-JKI 3.9 RADAR
LOCALIZER 111.95 I-JKI Chan 56 (Y)
UNITED STATES
CANADA
795
863

216° (3.1) 4000 3000 2000

1100 4000 DXO R-297 DOHNT INT

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| S-ILS 22R* | 842/24 | 200 (200-½) | | |

ELEV 645 D TDZE 642




TDZ/CL Rwys 3R, 4L, 4R and 22R
REIL Rwys 3L, 9L, 9R and 21R
HIRL all Rwys



EC-1, 19 MAR 2026 to 16 APR 2026
EC-1, 19 MAR 2026 to 16 APR 2026