

CHICAGO, ILLINOIS

AL-166 (FAA)


RNAV (GPS) PRM Y RWY 28L
(CLOSE PARALLEL)
CHICAGO O'HARE INTL (ORD)

25163



WAAS CH 93839 W28E	APP CRS 275°	Rwy Ldg TDZE 667 Apt Elev 680
--	------------------------	---

RNP APCH. RADAR required. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF comm required. See additional requirements on AAUP.	ALSIF-2 	MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 direct CGT VORTAC and hold.
---	-------------	--

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 133.0 348.0 PRM 128.05	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRs)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)	CLNC DEL 121.6	CPDLC
--	--	---	---	---	--------------------------	-------



ELEV 680	D	TDZE 667
-----------------	----------	-----------------



EC-3, 19 MAR 2026 to 16 APR 2026

EC-3, 19 MAR 2026 to 16 APR 2026