

(CONTINUED ON FOLLOWING PAGE)

MEMPHIS APP CON
119.1 291.6 (176°-355°)
125.8 338.3 (356°-175°)
D-ATIS 127.75

- NOTE: DME and RADAR required.
- NOTE: Procedure not available for RNAV capable Turboprops.
- NOTE: RNAV capable Turboprops must file the HOBKR RNAV STAR.
- NOTE: Maintain last assigned altitude until cleared to "descend via the MARVELL SIX," then comply with altitude restrictions as published.

TEXARKANA
116.3 TXK
Chan 110

EL DORADO
115.5 ELD
Chan 102

GREENVILLE
114.25 GLH
Chan 89(Y)

MARVELL
113.65 UJM
Chan 83(Y)

MEMPHIS
117.5 MEM
Chan 122
3000

TWIKL
11000
8000
210K

JAMEA
12000
10000
250K

MADDN
4000
052°
(4)
232°

BARFF
280K

OGONY
FL210 290K

TAMMY
10000 230K
16000 14000

ELLIN
FL210 290K

FENUR
FL210 290K

SIDON
114.7 SQS
Chan 94



NOTE: Chart not to scale.

MARVELL SIX ARRIVAL
(UJM, UJM6) 10NOV16

FREDERICK W SMITH INTL/MEMPHIS (MEM)
MEMPHIS, TENNESSEE

(UJM, UJM6) 26078
MARVELL SIX ARRIVAL

AL-253 (FAA)
FREDERICK W SMITH INTL/MEMPHIS (MEM)
MEMPHIS, TENNESSEE

ARRIVAL ROUTE DESCRIPTION

EL DORADO TRANSITION (ELD.UJM6): From over ELD VOR/DME on ELD R-048 to FAYEE, then on UJM R-228 to UJM VOR/DME. Thence. . . .

GREENVILLE TRANSITION (GLH.UJM6): From over GLH VOR/DME on GLH R-360 to BARFF, then on UJM R-228 to UJM VOR/DME. Thence. . . .

SIDON TRANSITION (SQS.UJM6): From over SQS VORTAC on SQS R-328 to BARFF, then on UJM R-228 to UJM VOR/DME. Thence. . . .

TEXARKANA TRANSITION (TXK.UJM6): From over TXK VORTAC on TXK R-071 to FAYEE, then on UJM R-228 to UJM VOR/DME. Thence. . . .

TURBOJETS/TURBOPROPS LANDING SOUTH: From over UJM VOR/DME on MEM VORTAC R-232 to cross TAMMY/MEM 39 DME at or above 14000 and at or below 16000, then on MEM VORTAC R-232 to MADDN/MEM 29 DME, then on MEM VORTAC R-232 to JAMEA/MEM 19 DME at or above 10000 and at or below 12000 at 250K, then on MEM VORTAC R-232 to cross TWIKL/ MEM 8 DME at or above 8000 and at or below 11000 and at 210K, then on heading 355°, expect radar vectors to final approach course.

TURBOJETS/TURBOPROPS LANDING NORTH: From over UJM VOR/DME on MEM VORTAC R-232 to cross TAMMY/MEM 39 DME at 10000 and at 230K, then on heading 055, expect radar vectors to final approach course.

NON-TURBINE AIRCRAFT ALL RUNWAYS: From over UJM VOR/DME on MEM VORTAC R-232 to cross MEM VORTAC at or above 3000, expect radar vectors to final approach course after passing TAMMY/MEM 39 DME.

SE-1, 19 MAR 2026 to 16 APR 2026

SE-1, 19 MAR 2026 to 16 APR 2026