TOP ALTITUDE: ASSIGNED AT ATC

RNAV-1 DME/DME/IRU or GPS.
RADAR required.

DETROIT DEP CON
132.35 284.0
ATIS
125.025
CLNC DEL
118.25
GND CON
121.9
PONTIAC TOWER ★
120.5 (CTAF)

275° — 095°

SMUUV — 8000 *2600 279° (52) — IIICE — 8000 *3000 279° (15) — KAYLN — 279° (13) — MTRCT

N

MSA PTK 25 NM
2900

NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.

TAKEOFF MINIMUMS:
Rwy 9L/R, 27L/R: Standard.
Rwy 18, 36: NA-Environmental.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned by ATC, thence....
TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned by ATC, thence....

....for RADAR vectors to MTRCT, then on track 279° to KAYLN, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

SMUUV TRANSITION (KAYLN3.SMUUV):

(KAYLN3.KAYLN) 24137
KAYLN THREE DEPARTURE (RNAV) AL-5052 (FAA)
OAKLAND COUNTY INTL (PTK)
PONTIAC, MICHIGAN