APP CRS	Rwy Ldg	8605
168°	TDZE	27
	Apt Elev	27

RNAV (RNP) Z RWY 17L

SACRAMENTO INTL (SMF)

RNP AR APCH-GPS.

For uncompensated Baro-VNAV systems, procedure NA below -2°C or above 54°C. For inop ALS, increase RNP 0.12 all Cats visibility to RVR 4000; increase RNP 0.30 all Cats visibility to RVR 4500.

MALSR

MISSED APPROACH: Climb to 500 then right turn to 3000 direct GRIME and hold.
*Missed approach requires minimum climb of 290 feet per NM to 3000.
#Missed approach requires minimum climb of 300 feet per NM to 3000.

D-ATIS	NORCAL APP CON	CAPITOL TOWER	GND CON
126.75	125.4 259.1 (W-NE) 125.25 257.9 (SW) 127.4 317.5 (E-SE)	125.7 256.7	121.7 256.7







TDZL/RCLS Rwys 17L and 17R
HIRL Rwys 17R-35L and 17L-35R



CATEGORY	A	B	C	D
RNP 0.12 DA#	277/24 250 (300-½)			
RNP 0.30 DA*	339/24 312 (400-½)			

AUTHORIZATION REQUIRED

SW-2, 19 MAR 2026 to 16 APR 2026
SW-2, 19 MAR 2026 to 16 APR 2026