

WAAS CH <b>45905</b> <b>W22A</b>	APP CRS <b>215°</b>	Rwy Ldg <b>7193</b> TDZE <b>26</b> Apt Elev <b>26</b>
--	------------------------	---

# RNAV (GPS) RWY 22


PUNTA GORDA (PGD)

RNP APCH.



**⚠** Baro-VNAV NA when using Page Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. When local altimeter setting not received, use Page Fld altimeter setting and increase LPV DA to 276, LNAV/VNAV DA to 360, and all MDAs 60 feet; increase LNAV Cats C and D visibility ¼ SM, and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct BULOW and hold.

ATIS <b>135,675</b>	FORT MYERS APP CON★ <b>127.05 306.2</b>	PUNTA GORDA TOWER★ <b>121.0 (CTAF) 0</b>	GND CON <b>119.55</b>	UNICOM <b>122,975</b>
------------------------	--	---	--------------------------	--------------------------



ELEV 26	<b>D</b>	TDZE 26
---------	----------	---------



CATEGORY	A	B	C	D
LPV DA		226-3/4	200 (200-3/4)	
LNAV/VNAV DA		310-1	284 (300-1)	
LNAV MDA	420-1	394 (400-1)	420-1 1/8	394 (400-1 1/8)
CIRCLING	460-1 434 (500-1)	580-1 554 (600-1)	600-1 1/2 574 (600-1 1/2)	740-2 1/4 714 (800-2 1/4)