

(CLOSE PARALLEL)

CHICAGO O'HARE INTL (ORD)

WAAS CH <b>93839</b> <b>W28E</b>	APP CRS <b>275°</b>	Rwy Ldg TDZE <b>7500</b> <b>667</b>	Apt Elev <b>680</b>
----------------------------------------	------------------------	-------------------------------------------	------------------------


RNP APCH. RADAR required.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF comm required. See additional requirements on AAUP.



ALSIF-2

MISSED APPROACH: Climb to 1200 then climbing left turn to 4000 direct CGT VORTAC and hold.

D-ATIS <b>135.4</b> <b>282.225</b>	CHICAGO APP CON <b>119.0 292.125</b>	O'HARE TOWER <b>133.0 348.0</b> <b>PRM 128.05</b>	GND CON (TWR NORTH) <b>124.125</b> (TWR SOUTH) <b>118.05</b> <b>226.675</b> (ALL TWRS)	(TWR CENTER) (OBND) <b>121.75</b> (IBND) <b>121.9</b>	CLNC DEL <b>121.6</b>	CPDLC
------------------------------------------	-----------------------------------------	---------------------------------------------------------	----------------------------------------------------------------------------------------------------	----------------------------------------------------------------	--------------------------	-------



ELEV <b>680</b>	<b>D</b>	TDZE <b>667</b>
-----------------	----------	-----------------



CATEGORY	A	B	C	D
LPV DA		917/24	250 (300-½)	
LNAV/VNAV DA		1090/40	423 (500-¾)	

EC-3, 16 APR 2026 to 14 MAY 2026

EC-3, 16 APR 2026 to 14 MAY 2026