# ILS Y or LOC Y RWY 27

HELENA RGNL (HLN)

| LOC I-HLN | APP CRS | Rwy Ldg | 9000 |
|---|---|---|---|
| 110.1 | 271° | TDZE | 3852 |
| | | Apt Elev | 3877 |

ADF or RADAR required for procedure entry. ADF or DME required.

Circling NA to Rwys 10 and 28. Circling Rwy 5, 23, 35 NA at night. Inop table does not apply to S-LOC 27 all Cats. For inop ALS, increase S-ILS 27 all Cats visibility to 1⅞ SM, ORYON fix minimums: S-LOC 27 Cat C/D/E visibility to 2 SM. Holding at HAU NDB authorized for Cat A and B aircraft only. Circling NA for Cats D and E south of Rwy 9-27.
*DME from HLN VORTAC. DME use requires simultaneous reception of I-HLN and HLN DME.

-16°C

MALSR

MISSED APPROACH: Climb to 4700 then climbing right turn to 9300 on heading 021° and on HLN VORTAC R-340 to WOKEN INT and hold, continue climb-in-hold to 9300.

| ATIS | HELENA APP CON* | HELENA TOWER* | GND CON | UNICOM |
|---|---|---|---|---|
| 120.4 | 119.5 229.4 | 118.3 (CTAF) L 257.8 | 121.9 | 122.95 |







| CATEGORY | A | B | C | D | E |
|---|---|---|---|---|---|
| S-ILS 27 | 4496-1⅜ 644 (700-1⅜) | | | | |
| S-LOC 27 | 5640-1¼ 1788 (1800-1¼) | 5640-1½ 1788 (1800-1½) | 5640-3 1788 (1800-3) | | |
| CIRCLING | 5640-1¼ 1763 (1800-1¼) | 5640-1½ 1763 (1800-1½) | 6000-3 2123 (2200-3) | | |
| ORYON FIX MINIMUMS* | | | | | |
| S-LOC 27 | 4600-½ 748 (800-½) | 4600-¾ 748 (800-¾) | 4600-1¾ 748 (800-1¾) | | |
| CIRCLING | 4640-1 763 (800-1) | 4800-1¼ 923 (1000-1¼) | 6000-3 2123 (2200-3) | | |

ELEV 3877 D TDZE 3852




REIL Rwys 9, 17 and 35 L
MIRL Rwys 5-23 and 17-35 L
HIRL Rwy 9-27 L

FAF to MAP 8.7 NM

| Knots | 60 | 90 | 120 | 150 | 180 |
|---|---|---|---|---|---|
| Min:Sec | 8:42 | 5:48 | 4:21 | 3:29 | 2:54 |



NW-1, 16 APR 2026 to 14 MAY 2026
NW-1, 16 APR 2026 to 14 MAY 2026