RNAV (RNP) Z RWY 18R

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

APP CRS	Rwy Ldg	8000
186°	TDZE	868
	Apt Elev	896

RNP AR APCH - GPS. Authorization required. From RANGL or TARZI: RF

For uncompensated Baro-VNAV systems, procedure NA below -13°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 5500.

ALSF-2

MISSED APPROACH: Climb to 3000 direct BEPEE and on track 269° to AVIEW and hold.

D-ATIS	CINCINNATI APP CON	CINCINNATI TOWER	GND CON
134.375	119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	118.975 360.85 (18L/36R) 118.3 (9/27, 18C/36C) 133.325 (18R/36L)	121.7









CATEGORY	A	B	C	D
RNP 0.30 DA	1238/35		370 (400-⅝)	

HIRL all rwys
TDZL/RCLS all rwys except 27

AUTHORIZATION REQUIRED

SE-1, 16 APR 2026 to 14 MAY 2026
SE-1, 16 APR 2026 to 14 MAY 2026