


LOC/DME I-RNE	APP CRS	Rwy Ldg	5765
109.1	059°	TDZE	38
Chan 28		Apt Elev	47

ILS or LOC RWY 6



NANTUCKET MEML (ACK)

▼ Inop table does not apply to S-ILS 6. For inop ALS, increase S-LOC 6 all Cats visibility to RVR 5000.

▲ MALSF 

MISSED APPROACH: Climb to 1800 direct ACK VOR/DME and hold, continue climb-in-hold to 1800.

ATIS 127.5	BOSTON APP CON 126.1 318.1	NANTUCKET TOWER ★ 118.3 (CTAF) 0	GND CON 132.5	UNICOM 122.95
----------------------	--------------------------------------	--	-------------------------	-------------------------



ELEV 47	D	TDZE 38
---------	---	---------

TWR ★ 51

4500 X 100

2303 X 150

0.5% Up

059°

TDZL/RCLS Rwy 24

REIL Rws 15 and 33

MIRL Rwy 15-33 0

HIRL Rwy 6-24 0

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

CATEGORY	A	B	C	D
S-ILS 6		238/40	200 (200-¾)	
S-LOC 6		380/40	342 (400-¾)	
CIRCLING	480-1 433 (500-1)	500-1 453 (500-1)	720-2 673 (700-2)	720-2¼ 673 (700-2¼)

NE-1, 16 APR 2026 to 14 MAY 2026

NE-1, 16 APR 2026 to 14 MAY 2026