WAAS	APP CRS	Rwy Idg	5998
CH 40420	178°	TDZE	206
W18A		Apt Elev	206

RNAV (GPS) RWY 18

PINEBLUFF RGNL/GRIDER FLD (PBF)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using Stuttgart altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. When local altimeter setting not received, use Stuttgart altimeter setting and increase LPV DA to 534 feet; increase LNAV/VNAV DA to 723 feet and all visibilities 1/8 SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D 3/8 SM, and Circling visibility Cat C/D 1/4 SM. For inop ALS, increase LNAV Cats A/B visibility to 1 SM and Cats C/D visibility to 1 1/8 SM. For inop ALS when using Stuttgart altimeter setting, increase LPV all Cats visibility to 1 SM; increase LNAV/VNAV all Cats visibility to 1 3/8 SM; increase LNAV Cats C/D visibility 1 3/8 SM.

MALSR

MISSED APPROACH: Climb to 2000 direct REROY and hold.

ASOS	LITTLE ROCK APP CON	CLNC DEL	UNICOM
120.775	119.85 353.6	119.85	123.0 (CTAF)







CATEGORY	A	B	C	D
LPV DA	459-3/4 253 (300-3/4)			
LNAV/VNAV DA	648-1 442 (500-1)			
LNAV MDA	600-3/4 394 (400-3/4)			
CIRCLING	660-1 454 (500-1)	680-1 474 (500-1)	840-1 3/4 634 (700-1 3/4)	880-2 1/4 674 (700-2 1/4)

SC-1, 16 APR 2026 to 14 MAY 2026
SC-1, 16 APR 2026 to 14 MAY 2026