

LOC I-MSS <b>108.7</b>	APP CRS <b>045°</b>	Rwy Ldg <b>5601</b>
		TDZE <b>205</b>
		Apt Elev <b>221</b>

# ILS or LOC RWY 5



MASSENA INTL-RICHARDS FLD (MSS)

ADF required. ADF and RADAR required for procedure entry.

**NA** Circling Rwy 9, 23, 27 NA at night. When local altimeter setting not received, use PTD altimeter setting: increase S-ILS 5 DA to 528 feet and all visibilities ¼ SM; increase all MDAs 80 feet and S-LOC 5 visibility Cats C and D ½ SM, and Circling visibility Cats C and D ¼ SM.

**MISSED APPROACH:**  
Climb to 1200 then climbing left turn to 2300 direct MISSE LOM and hold.

ASOS <b>128.075</b>	BOSTON CENTER <b>135.25 377.1</b>	UNICOM <b>123.0 (CTAF) 0</b>
------------------------	--------------------------------------	---------------------------------



ELEV 221	TDZE 205
REIL Rwys 5, 9 and 27	
HIRL Rwy 5-23	
MIRL Rwy 9-27	

4000 X 100

5601 X 100

0.3% UP

045°

5

27

9

5

CATEGORY	A	B	C	D
S-ILS 5	455-¾ 250 (300-¾)			
S-LOC 5	800-1	595 (600-1)	800-1¾	595 (600-1¾)
CIRCLING	800-1	579 (600-1)	880-1¾	900-2¼
			659 (700-1¾)	679 (700-2¼)

FAF to MAP 5.4 NM					
Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

NE-2, 16 APR 2026 to 14 MAY 2026

NE-2, 16 APR 2026 to 14 MAY 2026