


LOC/DME I-ANC 111.3 Chan 50	APP CRS 074°	Rwy Ldg 12400 TDZE 132 Apt Elev 151	7R 10600 128 151	7L
---	------------------------	--	--	----

ILS or LOC RWY 7R
TED STEVENS ANCHORAGE INTL (ANC) (PANC)

DME required. ▼ ▲ ❄ -21°C	For inop ALS, increase S-ILS 7R Cat E visibility to RVR 4000, S-LOC 7R Cat E visibility to RVR 6000, and Sidestep Rwy 7L Cat E visibility to 2 SM. Rwy 7L threshold 6140 feet east of Rwy 7R threshold.	ALSIF-2 Rwy 7R ▲	MALSR Rwy 7L ▲	MISSED APPROACH: Climb to 780 then climbing right turn to 3000 on heading 230° and on TED VOR/DME R-210 to JUKEP/TED 15 DME and hold. (TACAN aircraft climb to 780 then climbing right turn to 3000 on heading 230° and EDF TACAN R-210 to JUKEP/EDF 22.6 DME and hold).
------------------------------------	---	---------------------	-------------------	--

D-ATIS 135.5	ANCHORAGE APP CON 118.6 290.5	ANCHORAGE TOWER 118.3 257.8	GND CON 121.9 338.25	CLNC DEL 119.4 323.1
------------------------	---	---------------------------------------	--------------------------------	--------------------------------



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).				
ELIAS INT I-ANC 18.6	WEWVO I-ANC 12.4	TULLI I-ANC 6.7	WVDA I-ANC 4.8	JUKEP I-ANC 2.2
2000	3300	1600	1000	
GS 3.00° TCH 55	6.3 NM	5.7 NM	1.8 NM	1.6 NM
CATEGORY	A	B	C	D
S-ILS 7R	332/18 200 (200-½)			
S-LOC 7R	520/24	388 (400-½)	520/35	388 (400-¾)
SIDESTEP 7L	520/55	392 (400-1)	520-1½	392 (400-1½)
CIRCLING	700-1	549 (600-1)	800-1¾	920-2½
		649 (700-1¾)	769 (800-2½)	769 (800-2¾)