

APP CRS	Rwy Ldg	6500
354°	TDZE	544
	Apt Elev	544

RNAV (GPS) RWY 35


ST LOUIS RGNL (ALN)

RNP APCH.



▼ Visibility reduction by helicopters NA. When local altimeter setting not received, use St Louis Lambert Intl altimeter setting and increase all MDA 60 feet, increase LNAV Cat C/ D visibility 1/8 SM and Circling Cat C/D visibility 1/4 SM. When VGSi inop, straight-in/ Circling Rwy 35 procedure and Circling Rwy 17 NA at night.

MISSED APPROACH: Climb to 2200 direct JETIK and hold.

ATIS 128.0	ST LOUIS APP CON 124.2 353.9	REGIONAL TOWER* 126.0 (CTAF) 0 239.0	GND CON 120.2	UNICOM 122.95
----------------------	--	--	-------------------------	-------------------------



ELEV 544	D	TDZE 544
----------	----------	----------



CATEGORY	A	B	C	D
LNAV MDA	1020-1	476 (500-1)	1020-1 3/8	476 (500-1 3/8)
CIRCLING	1020-1	476 (500-1)	1160-1 3/4 616 (700-1 3/4)	1200-2 656 (600-2)

EC-3, 16 APR 2026 to 14 MAY 2026

EC-3, 16 APR 2026 to 14 MAY 2026