

WAAS CH 77836 W22A	APP CRS 217°	Rwy Ldg TDZE Apt Elev	4997 1119 1119
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 22

THIEF RIVER FALLS RGNL (TVF)



⚠ Baro-VNAV and VDP NA when using Crookston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Crookston altimeter setting and increase all DA 82 feet and all MDA 100 feet. Increase LPV all Cats visibility to 1 1/8 mile and LNAV/VNAV all Cats visibility to 1 1/4 mile.

MISSED APPROACH:
Climb 3300 direct
BOOMS and hold.

AWOS-3PT 119.025	MINNEAPOLIS CENTER 132.15 269.6	UNICOM 122.8 (CTAF) 1
----------------------------	---	---------------------------------



ELEV 1119 **D** TDZE 1119



CATEGORY	A	B	C	D
LPV DA	1369-1	250 (300-1)		NA
LNAV/VNAV DA	1396-1	277 (300-1)		NA
LNAV MDA	1500-1	381 (400-1)		NA
CIRCLING	1540-1	1580-1		NA
	421 (500-1)	461 (500-1)		

HIRL Rwy 13-31 **1**
MIRL Rwy 4-22 **1**
REIL Rws 4, 13 and 22 **1**

NC-1, 16 APR 2026 to 14 MAY 2026

NC-1, 16 APR 2026 to 14 MAY 2026