

WAAS CH 45533	APP CRS 282°	Rwy Ldg TDZE Apt Elev	3501 941 941
W28A			

RNAV (GPS) RWY 28


BROOKS FLD (RMY)

RNP APCH - GPS.



▼ Rwy 28 helicopter visibility reduction below 3/4 SM NA. Circling Rwy 10 NA at night.
 ▲ When local altimeter setting not received, use BTL altimeter setting: increase all MDAs 40 feet and increase LP and LNAV Cat C visibility 1/8 SM and Circling Cat C visibility 1/4 SM. VDP NA with BTL altimeter setting.

MISSED APPROACH: Climb to 1500 then climbing left turn to 3100 direct AWSOF and hold.

AWOS-3P 120.025	GREAT LAKES APP CON * 119.2 239.25	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



ELEV 941	TDZE 941
----------	----------



CATEGORY	A	B	C	D
LP MDA	1320-1		379 (400-1)	NA
LNAV MDA	1320-1		379 (400-1)	NA
CIRCLING	1440-1	499 (500-1)	1660-2 719 (800-2)	NA

EC-1, 16 APR 2026 to 14 MAY 2026

EC-1, 16 APR 2026 to 14 MAY 2026