

WAAS CH 42603 W05A	APP CRS 053°	Rwy Ldg TDZE Apt Elev	5001 798 802
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 5




LENAWEE COUNTY (ADG)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
⚠ When local altimeter setting not received, use Ann Arbor Muni altimeter setting; increase LPV all Cats DA to 1114 feet and all visibilities 1/8 SM; increase LNAV/VNAV all Cats DA to 1185 feet; increase all MDA 80 feet and visibility LNAV Cats C/D 1/4 SM. Baro-VNAV and VDP NA when using Ann Arbor Muni altimeter setting.

MISSED APPROACH:
Climb to 3000 direct EZHAF and hold.

ASOS 118.825	TOLEDO APP CON 134.35 317.55	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA		1048-3/4	250 (300-3/4)	
LNAV/VNAV DA		1119-1/4	321 (400-1/4)	
LNAV MDA	1200-1	402 (400-1)	1200-1/4	402 (400-1/4)

EC-1, 16 APR 2026 to 14 MAY 2026

EC-1, 16 APR 2026 to 14 MAY 2026