WAAS	APP CRS		
CH **90237**	**028°**	Rwy Ldg	**3701**
W03A		TDZE	**2595**
		Apt Elev	**2595**

RNAV (GPS) RWY 3

MILLER FLD (VTN)

Baro-VNAV NA when using Ainsworth Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Ainsworth Rgnl altimeter setting. When local altimeter setting not received, use Ainsworth Rgnl altimeter setting and increase all DA 70 feet and all MDA 80 feet, increase LNAV/VNAV Cat A/B visibility ⅛ mile.

MISSED APPROACH: Climb to 5000 direct MAIMS and hold.

ASOS	DENVER CENTER	UNICOM
118.075	**127.95 338.2**	**122.8** (CTAF) L





CATEGORY	A	B	C	D
LPV DA	2845-1	250 (300-1)	NA	
LNAV/VNAV DA	2845-1	250 (300-1)	NA	
LNAV MDA	2920-1	325 (400-1)	NA	
CIRCLING	3080-1 485 (500-1)	3560-1½ 965 (1000-1½)	NA	

ELEV 2595 TDZE 2595



REIL Rwy 32 L
MIRL Rwys 3-21 and 14-32 L

NC-2, 16 APR 2026 to 14 MAY 2026
NC-2, 16 APR 2026 to 14 MAY 2026