



LOC/DME I-OLV <b>109.3</b> Chan 30	APP CRS <b>181°</b>	Rwy Ldg TDZE Apt Elev	<b>6000</b> <b>402</b> <b>402</b>
--	------------------------	-----------------------------	---

**ILS or LOC RWY 18**  
OLIVE BRANCH/TAYLOR FLD (OLV)




**⚠** When local altimeter setting not received, use Frederick W Smith Intl altimeter setting and increase all DA 32 feet and all MDA 40 feet, increase S-LOC 18 Cats C and D visibility 1/8 mile and Circling Cats C and D visibility 1/4 mile; increase WIMUB fix minimums Circling Cats C and D visibility 1/4 mile.

**MALSR**  
  
MISSED APPROACH: Climb to 1100 then climbing left turn to 2500 on heading 074° and on MEM VORTAC R-102 to ZAMXU INT/MEM 25.7 DME and hold.

ATIS <b>119.925</b>	MEMPHIS APP CON <b>125.8 338.3</b>	OLIVE BRANCH TOWER ★ <b>125.275 (CTAF) 0</b>	GND CON <b>121.2</b>	UNICOM <b>122.95</b>
------------------------	---------------------------------------	---	-------------------------	-------------------------

ALTERNATE MISSED APCH FIX  
**HOLLY SPRINGS**  
HLI 112.4  
Chan 71  


**GPS REQUIRED FOR TAA**



CATEGORY	A	B	C	D
S-ILS 18	602-1/2 200 (200-1/2)			
S-LOC 18	860-1/2 458 (500-1/2)	860-7/8 458 (500-7/8)		
CIRCLING	1060-1 658 (700-1)	1060-1 3/4 658 (700-1 3/4)		1200-2 1/2 798 (800-2 1/2)
WIMUB FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 18	760-1/2 358 (400-1/2)	760-5/8 358 (400-5/8)		
CIRCLING	1060-1 658 (700-1)	1060-1 3/4 658 (700-1 3/4)		1200-2 1/2 798 (800-2 1/2)

SC-4, 16 APR 2026 to 14 MAY 2026

SC-4, 16 APR 2026 to 14 MAY 2026