

# KEENE SIX DEPARTURE

### LONE STAR DEP CON

135.975 379.9 (Rwys 13L/R, 17L/C/R, 18L/R)

118.1 306.95 (Rwys 31L/R, 35L/C/R, 36L/R)

D-ATIS DEP

135.925

CLNC DEL

128.25

CPDLC

GND CON

121.65 121.8 (EAST)

121.85 (WEST)



DFW TOWER

126.55 127.5 (EAST)

124.15 134.9 (WEST)

RADAR required.

**TOP ALTITUDE:  
2000**



WACO  
115.3 ACT Chan 100

ELLVR

WINDU

TORNN

BILEE

COLLEGE STATION  
113.3 CLL Chan 80

NAVASOTA  
115.9 TNV Chan 106

NOTE: For non-Turbojet aircraft.  
NOTE: JASPA TRANSITION: ATC assigned.

### TAKEOFF MINIMUMS

Rwys 13L/R, 17L/C/R, 18L/R, 31L/R, 35L/C, 36L/R: Standard.

Rwy 35R: 300-1<sup>3</sup>/<sub>4</sub> or standard with minimum climb of 230'/NM to 800, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1700' prior to DER.

NOTE: Chart not to scale.



### DEPARTURE ROUTE DESCRIPTION

#### NON-TURBOJET AIRCRAFT ONLY

TAKEOFF RUNWAYS 13L/R, 17L/C/R, 18L/R: Climb on heading 240° for RADAR vectors to appropriate FIX, maintain 2000 and expect filed altitude 10 minutes after departure.

TAKEOFF RUNWAYS 31L/R, 35L/C/R, 36L/R: Climb on heading 270° for RADAR vectors to appropriate FIX, maintain 2000 and expect filed altitude 10 minutes after departure.

# KEENE SIX DEPARTURE