

LOC I-BGE <b>111.35</b>	APP CRS <b>274°</b>	Rwy Idg <b>5502</b>
		TDZE <b>134</b>
		Apt Elev <b>141</b>


# ILS or LOC RWY 27

DECATUR COUNTY INDUSTRIAL AIR PARK (BGE)



**NA** ADF required. When local altimeter setting not received, use Tallahassee Intl altimeter setting and increase S-ILS 27 DA to 429 feet and all MDA 100 feet; increase S-LOC 27 visibility Cat C, D ¼ SM and Circling Cat C, D visibility ½ SM. For inop MALS, when using Tallahassee Intl altimeter setting increase S-ILS 27 all Cats visibility to 1 mile.

**MALS** MISSED APPROACH: Climb to 1200 then climbing right turn to 1900 direct LYZ NDB and hold.

AWOS-3PT <b>121.125</b>	TALLAHASSEE APP CON* <b>128.7 254.3</b>	CLNC DEL <b>124.775 335.65</b>	UNICOM <b>122.975</b> (CTAF)
----------------------------	--	-----------------------------------	---------------------------------



ELEV 141	TDZE 134
----------	----------



CATEGORY	A	B	C	D
S-ILS 27	334-½		200 (200-½)	
S-LOC 27	480-½		346 (400-½)	
CIRCLING	600-1		459 (500-1)	
			800-1¾	
			659 (700-1¾)	
			860-2¼	
			719 (800-2¼)	

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

SE-4, 16 APR 2026 to 14 MAY 2026

SE-4, 16 APR 2026 to 14 MAY 2026