


LOC/DME I-RYY 111.9 Chan 56	APP CRS 273°	Rwy Idg TDZE Apt Elev	5374 1011 1040
---	------------------------	-----------------------------	---

ILS or LOC RWY 27

COBB COUNTY INTL/MCCOLLUM FLD (RYY)

DME required. RADAR required for procedure entry.		MALSIF	MISSED APPROACH: Climb to 1600 then climbing right turn to 3500 on heading 300° and on RMG VORTAC R-108 to TIPPY/RMG 11 DME and hold.
Inop table does not apply to S-ILS 27.			


ATIS 128.125	ATLANTA APP CON 121.0 268.7	MCCOLLUM TOWER ★ 125.9 (CTAF) 0	GND CON 119.0	CLNC DEL 119.0	CLNC DEL 121.0 268.7 (When twr closed)	UNICOM 122.7
------------------------	---------------------------------------	---	-------------------------	--------------------------	---	------------------------



SE-4, 16 APR 2026 to 14 MAY 2026

SE-4, 16 APR 2026 to 14 MAY 2026

ELEV 1040	D	TDZE 1011
-----------	----------	-----------



HIRL Rwy 9-27 0 FAF to MAP 6.1 NM Knots: 60 90 120 150 180 Min:Sec: 6:06 4:04 3:03 2:26 2:02	<table border="1"> <tr> <td>CATEGORY</td> <td>A</td> <td>B</td> <td>C</td> <td>D</td> </tr> <tr> <td>S-ILS 27</td> <td colspan="4">1211-3/4 200 (200-3/4)</td> </tr> <tr> <td>S-LOC 27</td> <td>1620-3/4</td> <td>609 (600-3/4)</td> <td>1620-1/2</td> <td>609 (600-1/2)</td> </tr> <tr> <td>C CIRCLING</td> <td>1800-1</td> <td>760 (800-1)</td> <td>2180-3</td> <td>1140 (1200-3)</td> </tr> <tr> <td colspan="5" style="text-align: center;">CUMAV FIX MINIMUMS</td> </tr> <tr> <td>S-LOC 27</td> <td>1480-3/4</td> <td>469 (500-3/4)</td> <td>1480-1 1/8</td> <td>469 (500-1 1/8)</td> </tr> <tr> <td>C CIRCLING</td> <td>1800-1</td> <td>760 (800-1)</td> <td>2180-3</td> <td>1140 (1200-3)</td> </tr> </table>	CATEGORY	A	B	C	D	S-ILS 27	1211-3/4 200 (200-3/4)				S-LOC 27	1620-3/4	609 (600-3/4)	1620-1/2	609 (600-1/2)	C CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)	CUMAV FIX MINIMUMS					S-LOC 27	1480-3/4	469 (500-3/4)	1480-1 1/8	469 (500-1 1/8)	C CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)
CATEGORY	A	B	C	D																																
S-ILS 27	1211-3/4 200 (200-3/4)																																			
S-LOC 27	1620-3/4	609 (600-3/4)	1620-1/2	609 (600-1/2)																																
C CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)																																
CUMAV FIX MINIMUMS																																				
S-LOC 27	1480-3/4	469 (500-3/4)	1480-1 1/8	469 (500-1 1/8)																																
C CIRCLING	1800-1	760 (800-1)	2180-3	1140 (1200-3)																																