


WAAS CH 78213 W06A	APP CRS 064°	Rwy Ldg 4000 TDZE 54 Apt Elev 55
--	------------------------	---

RNAV (GPS) RWY 6

ROBERT/BOB/CURTIS MEML (D76) (PFNO)

RNP APCH.	MISSED APPROACH: Climb to 4400 direct MABYL and on track 032° to BARGN and hold, continue climb-in-hold to 4400.
▼ ▲ ⊞ Rwy 6 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.	

AWOS-3P 120.0	ANCHORAGE CENTER 119.2 263.0	CTAF 122.7 0
-------------------------	--	------------------------



VGSIs and RNAV glidepath not coincident (VGSIs Angle 3.00/TCH 25).				
4 NM Holding Pattern				
6000 ← 244° 2700 → 064°				
GP 3.00° TCH 40				
ODMEE				
FERKU				
GAHTI 3 NM to RW06				
*1020				
*1.2 NM to RW06				
*LNNAV only				
6 NM				
2.1 NM				
1.8 NM				
1.2 NM				
CATEGORY	A	B	C	D
LPV DA	304-1 250 (300-1)			
LNNAV/VNAV DA	355-1 301 (300-1)			
LNNAV MDA	460-1 406 (500-1)		460-1½ 406 (500-1½)	
CIRCLING	520-1 465 (500-1)		520-1½ 465 (500-1½)	
			760-2¼ 705 (800-2¼)	

