

# RADAR MINS

25359

N1

## RADAR INSTRUMENT APPROACH MINIMUMS

### BISMARCK, ND

Amdt 3C, 02DEC21 (21336) (FAA)

ELEV 1661

### BISMARCK MUNI (BIS)

RADAR-1 126.3 298.9 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	31		AB	2100/24	454	(500-½)	C	2100/40	454	(500-¾)
			D	2100/50	454	(500-1)				
	13		AB	2100-1	445	(500-1)	C	2100-1¼	445	(500-1¼)
			D	2100-1½	445	(500-1½)				
	21		AB	2160-1	499	(500-1)	CD	2160-1¾	499	(500-1¾)
	3		AB	2220-1	559	(600-1)	CD	2220-1¾	559	(600-1¾)
CIR	ALL RWY		AB	2220-1	559	(600-1)	C	2460-2¼	799	(800-2¼)
			D	2460-2½	799	(800-2½)				

Inoperative table does not apply to ALS Rwy 13.

### DULUTH, MN

Orig-A, 30JAN20 (21112) (FAA)

ELEV 1428

### DULUTH INTL (DLH)

RADAR-1 125.45 233.7 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	3		AB	1820-1	400	(400-1)	CDE	1820-1½	400	(400-1½)
			ABCDE	1820/40	392	(400-¾)				
			AB	1840-1	420	(500-1)	CDE	1840-1½	420	(500-1½)
			AB	1880/40	459	(500-¾)	CDE	1880/45	459	(500-¾)
CIR	ALL RWY		A	1880-1	452	(500-1)	B	1900-1	472	(500-1)
			C	1940-1½	512	(600-1½)	DE	2400-3	972	(1000-3)

Circling NA for CAT E SE of Rwys 3 and 27.

Rwy 3, 9, 21 helicopter visibility reduction below ¾ SM not authorized.

VGSI and descent angles not coincident.

For inoperative ALS, increase ASR S-09 Cats A/B visibility to RVR 5500, Cats C/D/E to 1½ SM.

For inoperative ALS, increase ASR S-27 Cats A/B visibility to RVR 5500, Cats C/D/E to 1½ SM.

16 APR 2026 to 14 MAY 2026

16 APR 2026 to 14 MAY 2026

NC-1

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS

25359

N1

# RADAR MINS

25359

N2

## RADAR INSTRUMENT APPROACH MINIMUMS

### MANDAN, ND

Amdt 5A, 18AUG16 (21224) (FAA)

ELEV 1994

### MANDAN RGNL/LAWLER FLD (Y19)

RADAR-1 126.3 298.9 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	31		AB	2440-1	499	(500-1)	CD	2440-1 <sup>3</sup> / <sub>8</sub>	499	(500-1 <sup>3</sup> / <sub>8</sub> )
	13		AB	2460-1	522	(600-1)	CD	2460-1 <sup>1</sup> / <sub>2</sub>	522	(600-1 <sup>1</sup> / <sub>2</sub> )
CIR	ALL RWY		AB	2460-1	516	(600-1)	C	2460-1 <sup>1</sup> / <sub>2</sub>	516	(600-1 <sup>1</sup> / <sub>2</sub> )
			D	2560-2	616	(700-2)				

ASR S-13: Helicopter visibility reduction below 3/4 SM not authorized.

ASR S-31: Helicopter visibility reduction below 3/4 SM not authorized.

When BIS control tower closed, ASR NA.

When local altimeter setting not received, use Bismarck altimeter setting and increase all MDA 60 feet, increase all CAT C/D visibility 1/4 mile.

Circling to Rwys 4 and 22 NA.

### SIoux FALLS, SD

Amdt 11A, 25DEC25 (25359) (FAA)

ELEV 1430

### JOE FOSS FLD (FSD)

RADAR-1 125.8 284.725 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	3		AB	1980/24	556	(600-1/2)	CDE	1980/60	556	(600-1/4)
	21		AB	2000/24	570	(600-1/2)	CDE	2000-1/4	570	(600-1/4)
	33		AB	2020-1	597	(600-1)	CDE	2020-1/4	597	(600-1/4)
	15		AB	2060-1	631	(700-1)	CDE	2060-1/4	631	(700-1/4)
CIR	ALL RWY		AB	2060-1	630	(700-1)	C	2060-1/4	630	(700-1/4)
			D	2200-2 <sup>1</sup> / <sub>2</sub>	770	(800-2 <sup>1</sup> / <sub>2</sub> )	E	2240-2 <sup>3</sup> / <sub>4</sub>	810	(900-2 <sup>3</sup> / <sub>4</sub> )

When control tower closed, ASR NA.

Rwy 15/33 helicopter visibility reduction below 3/4 SM not authorized.

For inoperative ALS increase ASR-3 Cat E visibility to 1% SM.

For inoperative ALS increase ASR-21 Cat C, D and E visibility to 1% mile.

16 APR 2026 to 14 MAY 2026

16 APR 2026 to 14 MAY 2026

NC-1

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS

25359

N2