RNAV (GPS) RWY 23

FORT WAYNE INTL (FWA)

WAAS CH 69599 W23A	APP CRS 230°	Rwy Ldg 11981 TDZE 799 Apt Elev 815

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3000 direct EBACO and hold.

ATIS	FORT WAYNE APP CON	FORT WAYNE TOWER	GND CON
121.25 360.825	127.2 284.6	119.1 269.325	121.9 348.6



ELEV 815 D TDZE 799



TDZL/RCLS Rwy 5
REIL Rwys 14 and 23
HIRL Rwys 5-23 and 14-32



CATEGORY	A	B	C	D	E
LPV DA	1053/40 254 (300-¾)				
LNAV/VNAV DA	1230-1⅜ 431 (500-1⅜)				
LNAV MDA	1300/55 501 (500-1)		1300-1⅜ 501 (500-1⅜)		
CIRCLING	1300-1 485 (500-1)		1420-1¾ 605 (700-1¾)	1520-2¼ 705 (800-2¼)	1520-2½ 705 (800-2½)

EC-2, 14 MAY 2026 to 11 JUN 2026
EC-2, 14 MAY 2026 to 11 JUN 2026