ILS or LOC RWY 10L

CHICAGO O'HARE INTL (ORD)

LOC/DME I-MED	APP CRS	Rwy Ldg 12246
111.1 Chan 48	093°	TDZE 672
		Apt Elev 680

From GIBNS: RNAV-1 GPS required.
RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
Simultaneous approach authorized.

ALSF-2

MISSED APPROACH: Climb to 4000 on heading 093° and CGT VORTAC R-336 to CGT VORTAC and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	132.7 348.0	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	

ALTERNATE MISSED APCH FIX
081° 114.55 DPA 261° R-081
Chan 92(Y)
BLUTO
DPA 41
RADAR

MSA ORD 25 NM
3400

NORTHBROOK
113.0 OBK
Chan 77

114.2 CGT R-336 Chan 89

R-184 R-197

LOCALIZER 111.1
I-MED
Chan 48

(IAF) GIBNS
ARIST I-MED 28.4 RADAR
KALZO I-MED 25.2 RADAR
BURKE I-MED 22.1 RADAR
SYSCO I-MED 18.9 RADAR
(IF) PRATT I-MED 15.8 RADAR
CARLE I-MED 12.7
BUGSE INT I-MED 7.3 RADAR
POPME INT I-MED 3.9

273° 8000 093° (3.1) 7000 (3.1) 6000 (3.1) 5000 (3.1) 4000 (3.1) 2300 093° (5.4)
9000 085° (20.3)
1468 883 IM 813 844 826 807 1508 1185

MISSED APCH FIX
CHICAGO HEIGHTS
CGT
114.2
Chan 89
156° 336° R-156

ELEV 680 D TDZE 672

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 74).

4000 hdg 093° CGT R-336 CGT

* LOC only.

GS 3.00°
TCH 56

	3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	5.4 NM	3.4 NM	1.4 NM	0.1
CATEGORY	A			B		C		D	
S-ILS 10L	872/18 200 (200-½)								
S-LOC 10L	1200/24 528 (600-½)					1200/55 528 (600-1)			
POPME FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)									
S-LOC 10L	1080/24 408 (400-½)					1080/40 408 (400-¾)			

HIRL all Rwys
TDZ/CL all Rwys except 4L

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

EC-3, 14 MAY 2026 to 11 JUN 2026
EC-3, 14 MAY 2026 to 11 JUN 2026