ILS Z or LOC Z RWY 10R

CHICAGO O'HARE INTL (ORD)

LOC/DME I-IZJ	APP CRS	Rwy Ldg	7500
110.75	094°	TDZE	680
Chan 44 (Y)		Apt Elev	680

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.
Simultaneous approach authorized.
For inop ALS, increase S-LOC 10R Cat C and D visibility to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	133.0 348.0	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	

ALTERNATE MISSED APCH FIX
JOLIET
JOT
112.3
Chan 70
R-246-066°
246°

MSA ORD 25 NM
3400
113.0 OBK
Chan 77
113.0 OBK
R-185
Chan 77
R-196

(IAF) GIBNS
SAFLY I-IZJ 27.7 RADAR
POPOF I-IZJ 24.6 RADAR
DAYZE I-IZJ 21.4 RADAR
BNITO I-IZJ 18.3 RADAR
(IF) BOOTR I-IZJ 15.2 RADAR
NIRRA I-IZJ 12 RADAR
KUULA INT I-IZJ 6.5 RADAR
ALYEA INT I-IZJ 3.4 RADAR
IM

8000
094°
(3.1)
7000
(3.1)
6000
(3.1)
5000
(3.1)
4000
(3.2)
2300
094°
(5.5)
274°
9000
087° (20.2)
1468
1508
1185
883
834
813

R-248-068°
248°
DUPAGE
114.55 DPA
Chan 92(Y)

LOCALIZER 110.75
I-IZJ
Chan 44(Y)

1200 4000 DPA
*LOC only

GS 3.00°
TCH 55
9000
8000
7000
6000
5000
4000
2300
*1220
*I-IZJ 2.7
I-IZJ 1.6

3.1 NM | 3.1 NM | 3.1 NM | 3.1 NM | 3.2 NM | 5.5 NM | 3.1 NM | 0.7 | 1 NM | 0.1

CATEGORY	A	B	C	D
S-ILS 10R	880/18 200 (200-½)			
S-LOC 10R	1100/24 420 (500-½)			

ELEV 680 D TDZE 680

7500 X 150
TWR
11245 X 200
0.3% DOWN
11260 X 150
13000 X 150
10800 X 200
0.3% UP
7500 X 150
094°

HIRL all Rwys
TDZ/CL all Rwys except 4L

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

EC-3, 14 MAY 2026 to 11 JUN 2026
EC-3, 14 MAY 2026 to 11 JUN 2026