

WAAS CH 60927 W22A	APP CRS 225°	Rwy Ldg 10006 TDZE 828 Apt Elev 842
--	------------------------	--

RNAV (GPS) RWY 22

MINNEAPOLIS-ST PAUL INTL/WOLD-CHAMBERLAIN (MSP)

RNP APCH

▼ Rwy 22 helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 5500, LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cat A/B visibility to RVR 5500, and Cat E to 1 ¼ SM.

MALSR



MISSED APPROACH: Climb to 3000 direct JOGTO and on track 159° to FGT VORTAC and hold.




D-ATIS 135.35 239.275

MINNEAPOLIS APP CON 118.725 335.65 (35) 119.3 335.65 (12L-30R, 4-22, 17) 126.95 335.65 (12R-30L)
--

MINNEAPOLIS TOWER 123.675 273.55 (17-35) 123.95 273.55 (12L-30R) 126.7 273.55 (12R-30L, 4-22)


GND CON 121.8 348.6 (N) 121.9 348.6 (S) 127.925 348.6 (W)

Procedure NA for arrivals at WHISK on V78 eastbound.



CATEGORY	A	B	C	D	E
LPV DA	1190/40 362 (400-¾)				
LNAV/VNAV DA	1227/45 399 (400-¾)				
LNAV MDA	1420/40 592 (600-¾)	1420-1¼ 592 (600-1¼)			
CIRCLING	1420-1 578 (600-1)	1460-1¾ 618 (700-1¾)	1660-2¾ 818 (900-2¾)	1800-3 958 (1000-3)	

ELEV 842	D TDZE 828
----------	-------------------



HIRL all rwys
REIL Rwy 17
TDZL/RCLS Rwy 12L, 12R, 30L, and 35

RNAV (GPS) RWY 22

NC-1, 14 MAY 2026 to 11 JUN 2026

NC-1, 14 MAY 2026 to 11 JUN 2026