


WAAS CH <b>78128</b> <b>W18A</b>	APP CRS <b>183°</b>	Rwy Ldg TDZE Apt Elev	<b>4376</b> <b>217</b> <b>219</b>
--	------------------------	-----------------------------	---

# RNAV (GPS) RWY 18

MOBILE RGNL (MOB)

RNP APCH - GPS.		MISSED APPROACH: Climb to 2000 direct IPAPE and hold.	
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 42°C. Rwy 18 helicopter visibility reduction below ¼ SM NA.			


ATIS <b>124.75 257.85</b>	MOBILE APP CON * <b>118.5 269.3</b>	MOBILE TOWER * <b>118.3 (CTAF) 239.0</b>	GND CON <b>121.9 348.6</b>	UNICOM <b>122.95</b>
------------------------------	--	---	-------------------------------	-------------------------



SE-4, 14 MAY 2026 to 11 JUN 2026

SE-4, 14 MAY 2026 to 11 JUN 2026

ELEV 219	TDZE 217
----------	----------



4 NM Holding Pattern		CECAP	BAKAY	DIDEC	RWY 18
6000 2000		2000	2000	1120	
GP 3.00° TCH 45					
		6.8 NM	2.8 NM	1.4 NM	1.3
CATEGORY	A	B	C	D	
LPV DA	508-1		291 (300-1)		
LNAV/VNAV DA	624-1 3/8		407 (500-1 3/8)		
LNAV MDA	640-1	423 (500-1)	640-1 1/4	423 (500-1 1/4)	
CIRCLING	680-1	461 (500-1)	740-1 1/2	780-2	561 (600-2)