ILS or LOC RWY 4

MONROE RGNL (MLU)

LOC I-MLU	APP CRS	Rwy Ldg	7504
109.5	042°	TDZE	78
		Apt Elev	79

ADF or DME required for procedure entry.

Circling Rwy 14 NA at night. For inop ALS, increase S-LOC 4 Cat C/D visibility to 1⅜ SM.

UXGOY FIX MINIMUMS: For inop ALS, increase S-LOC 4 Cat C/D visibility to RVR 5500.

ASR **RVR 1800 authorized with the use of FD or AP or HUD to DA.

DME from MLU VORTAC.

MALSR

MISSED APPROACH: Climb to 1800 then climbing right turn to 3000 direct MLU VORTAC and hold.

ATIS	MONROE APP CON ★	MONROE TOWER ★	GND CON	UNICOM
125.05	118.15 290.475	118.9 (CTAF) L 257.8	121.9	122.95

ALTERNATE MISSED APCH FIX

SABAR
MLU 5.1
ML
392

042° 222°

MSA ML LOM 25 NM
2200
050° 320°
3100

MONROE
117.2 MLU
Chan 119

170±
034°
214°
2000 to ML LOM
220° (5.1)
274
300
LOM/IAF
SABAR
392 ML
MLU 5.1
UXGOY
MLU 2.2
042°
(CFBJX)
R-221
357°
177°
222°

LOCALIZER 109.5
I-MLU

Remain within 10 NM
ML LOM MLU 5.1
222°
042°
2000
1483
1500
*540
UXGOY
MLU 2.2
* LOC only.
GS 3.00°
TCH 50
2.9 NM
1.3 NM

1800	3000	MLU

ELEV 79 D TDZE 78

TWR
14
32
22
4
7504 X 150
6301 X 150
042°

REIL Rwys 14 and 32
MIRL Rwy 14-32 L
HIRL Rwy 4-22 L

CATEGORY	A	B	C	D
S-ILS 4	**278/24 200 (200-½)			
S-LOC 4	540/24 462 (500-½)		540/50 462 (500-1)	
CIRCLING	580-1 501 (600-1)		740-1¾ 661(700-1¾)	1160-3 1081 (1100-3)
# UXGOY FIX MINIMUMS				
S-LOC 4	420/24 342 (400-½)		420/30 342 (400-⅝)	
CIRCLING	580-1 501 (600-1)		740-1¾ 661 (700-1¾)	1160-3 1081 (1100-3)

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

SC-4, 14 MAY 2026 to 11 JUN 2026
SC-4, 14 MAY 2026 to 11 JUN 2026