

PANAMA CITY, FLORIDA

RNAV (GPS) RWY 32R

| | | | |
|--------------------------|------------------|-------------------------------|--------------------|
| WAAS CH 52209 W32A | APCH CRS 319° | Rwy ldg TDZE Arprt Elev | 10,008 14 17 |
|--------------------------|------------------|-------------------------------|--------------------|

(USAF)

TYNDALL AFB (KPM)

RNP APCH - GPS

▼ * When ALS inop, increase RVR to 40, vis to 3/4 mile.
 ** When ALS inop, increase RVR to 55, vis to 1 mile.
 *** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1 3/8 miles.

ALSF-1



MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct SUSIE and hold.

| | | | | |
|----------------|---|-------------------------|------------------------|---------|
| ATIS★ 254.4 | APP CON/DEP CON★ 119.775 317.45 BLW 5000' 124.15 338.35 ABV 5000' | TOWER★ 133.95 263.15 | GND CON 121.9 259.3 | ASR/PAR |
|----------------|---|-------------------------|------------------------|---------|



For uncompensated Baro-VNAV systems, Procedure NA below 15°C (59°F) or above 54°C (130°F).

Average Cold Temperature based on standard -30.00°C ISA deviation.

SE-3, 14 MAY 2026 to 11 JUN 2026

SE-3, 14 MAY 2026 to 11 JUN 2026

EMERG SAFE ALT 100 NM 3300

| | | | | | |
|--------------------|---------------|---|---------------------------|---------|-------------|
| 600 crs 318° | 3000 SUSIE | VGSI and RNAV glidepath not coincident (VGSI 2.50/TCH 55) | BEAVS 3000 | ELEV 17 | TDZE 14 |
| | | | | | |
| CATEGORY | A | B | C | D | E |
| LPV DA* | 214/24 | | 200 | (200-½) | |
| LNAV/VNAV DA** | 362/30 | | 348 | (400-¾) | |
| LNAV MDA*** | 480/24 | 466 (500-½) | 480/50 | 466 | (500-1) |
| CIRCLING | 540-1 | 523 (600-1) | 540-1½ 523 (600-1½) | 580-2 | 563 (600-2) |

HIRL all rwys
Recommend Rwy 14L-32R for apch end engagement of A-Gear

PANAMA CITY, FLORIDA

30°04'N - 85°35'W

TYNDALL AFB (KPM)

Amdt 4 27NOV25

RNAV (GPS) RWY 32R