



LOC/DME I-VII 108.95 Chan 26(Y)	APP CRS 087°	Rwy Ldg TDZE Apt Elev	9500 13 36
--	------------------------	-----------------------------	---------------------------------------


ILS or LOC RWY 9L

PHILADELPHIA INTL (PHL)

▼ For inop ALS, increase S-LOC 9L Cat C/D visibility to 2 SM. ▲ * RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct OOD VORTAC and hold.	
			D-ATIS 133.4



ELEV 36	D TDZE 13
---------	------------------



CATEGORY	A	B	C	D
S-ILS 9L*	213/24 200 (200-½)			
S-LOC 9L	760/24 747 (800-½)	760/40 747 (800-¾)	760-1¾ 747 (800-1¾)	747 (800-1¾)
CIRCLING	760-1 724 (800-1)	760-1¼ 724 (800-1¼)	760-2 724 (800-2)	760-2¼ 724 (800-2¼)
LANDI FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 9L	440/24 427 (500-½)		440/40 427 (500-¾)	
CIRCLING	540-1 504 (600-1)	600-1 564 (600-1)	620-1½ 584 (600-1½)	720-2¼ 684 (700-2¼)

TDZ/CL Rwy 9R	HIRL all Rwys					
REIL Rwys 9L and 35	FAF to MAP 6.4 NM					
	Knots	60	90	120	150	180
	Min:Sec	6:24	4:16	3:12	2:34	2:08

NE-4, 14 MAY 2026 to 11 JUN 2026

NE-4, 14 MAY 2026 to 11 JUN 2026