WAAS CH 70514 W05A	APP CRS 046°	Rwy Ldg 7038 TDZE 3075 Apt Elev 3082

RNAV (GPS) Y RWY 5
ROBERTS FLD (RDM)

RNP APCH.

T A -16°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C.

MISSED APPROACH: Climb to 9500 direct COFMO and on track 136° to SAKKO and hold, continue climb-in-hold to 9500.

ATIS	SEATTLE CENTER	REDMOND TOWER ★	GND CON	UNICOM
119.025	126.15 269.475	124.5 (CTAF) L 256.8	121.8	122.95



ELEV 3082 D TDZE 3075





CATEGORY	A	B	C	D
LPV DA	3275-¾ 200 (200-¾)			
LNAV/VNAV DA	3347-⅞ 272 (300-⅞)			
LNAV MDA	3520-1 445 (500-1)		3520-1⅜ 445 (500-1⅜)	
CIRCLING	3540-1 458 (500-1)	3560-1 478 (500-1)	3640-1½ 558 (600-1½)	3740-2 658 (700-2)

REIL Rwys 5, 11, and 29 L
HIRL Rwy 5-23 L
MIRL Rwy 11-29 L

NW-1, 14 MAY 2026 to 11 JUN 2026

NW-1, 14 MAY 2026 to 11 JUN 2026