

LOC I-BKY 111.5	APP CRS 303°	Rwy Ldg 10679 TDZE 583 Apt Elev 617
---------------------------	------------------------	--

ILS or LOC RWY 30L


ST LOUIS LAMBERT INTL (STL)

▼ For inop ALS, increase S-ILS 30L Cat E visibility to RVR 4000 and S-LOC 30L Cat A/B visibility to RVR 5500 and cat C/D/E visibility to 1/2 SM. Simultaneous approach authorized with Rwy 30R requires use of vertical guidance; maintain last assigned altitude until established on glideslope. Simultaneous approach authorized with Rwy 29. LOC only: Rwy 30L helicopter visibility reduction below RVR 4000 NA. *RVR 1800 authorized with use of FD or AP or HUD to DA.




MISSED APPROACH: Climb to 2100 then climbing right turn to 3000 direct STL VORTAC and hold, continue climb-in-hold to 3000.

D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 118.5 257.7	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC
--	---	---------------------------------------	---	--------------------------------	-------




ELEV 617	D	TDZE 583
----------	----------	----------

Rwy 6-24 7603 X 150
Rwy 11-29 9000 X 150
Rwy 12L-30R 9013 X 150
Rwy 12R-30L 11020 X 150



HIRL all Rwsy
TDZ/CL Rwsy 11, 12L, 12R, 29, and 30R
FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38



CATEGORY	A	B	C	D	E
S-ILS 30L*	783/24 200 (200-1/2)				
S-LOC 30L	1100/40	517 (500-3/4)	1100/55	517 (500-1)	

NC-3, 14 MAY 2026 to 11 JUN 2026

NC-3, 14 MAY 2026 to 11 JUN 2026