RNAV (GPS) RWY 10L

PITTSBURGH INTL (PIT)

WAAS CH 81826 W10B	APP CRS 101°	Rwy Ldg 10502 / TDZE 1203 / Apt Elev 1203

RNP APCH - GPS.

Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV Cats C/D visibility to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1900 then climbing left turn to 4000 direct EWC VOR/DME and hold.

D-ATIS	PITTSBURGH APP CON	PITTSBURGH TOWER	GND CON
127.25	123.95 360.8	128.3 291.7	SOUTH 121.9 348.6 NORTH 127.8 348.6



ELEV 1203 D TDZE 1203





CATEGORY	A	B	C	D
LPV DA	1403/18 200 (200-½)			
LNAV/VNAV DA	1635/40 432 (500-¾)			
LNAV MDA	1620/24 417 (500-½)		1620/40 417 (500-¾)	
CIRCLING	1700-1 497 (500-1)		1880-2 677 (700-2)	1880-2¼ 677 (700-2¼)

REIL Rwy 10C
HIRL all rwys
TDZL/RCLS Rwys 10L, 10R, 28L, 28R, 28C, and 32

NE-4, 14 MAY 2026 to 11 JUN 2026
NE-4, 14 MAY 2026 to 11 JUN 2026