

LOC I-GKV 111.3	APP CRS 080°	Rwy Ldg TDZE Apt Elev	9318 469 469
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 8

FORT SMITH RGNL (FSM)

DME and RADAR required.



ASR

Circling NA for Cat E northwest of Rwy 8 and 20. Circling Rwy 20, 26 NA at night. For inop ALS, increase S-ILS 8 Cat E visibility to 3/4 SM, increase S-LOC 8, Cat C/D/E visibility to 1 1/2 SM. Circling NA for Cat E when restricted area R-2401B active. DME from FSM VORTAC. DME use requires simultaneous reception of I-GKV and FSM DME.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 3300 direct FSM VORTAC and hold, continue climb-in-hold to 3300. (TACAN aircraft continue climb to 4000 on FSM R-036 to FIGGS/10 DME/RADAR and hold NE, RT, 216° inbound, continue climb-in-hold to 4000.)

ATIS 124.775	RAZORBACK APP CON * 120.9 343.75	FORT SMITH TOWER * 118.3(CTAF) 323.175	GND CON 121.9 275.8	UNICOM 122.95
------------------------	--	---	-------------------------------	-------------------------



ELEV 469	D	TDZE 469						
<table border="1"> <tr> <td>1000</td> <td>3300</td> <td>FSM</td> </tr> <tr> <td>↑</td> <td>↷</td> <td>◻</td> </tr> </table>			1000	3300	FSM	↑	↷	◻
1000	3300	FSM						
↑	↷	◻						
GS 3.00°	TCH 52							
CATEGORY	A	B	C	D	E			
S-ILS 8	669-1/2		200 (200-1/2)					
S-LOC 8	880-1/2	411 (500-1/2)	880-3/4	411 (500-3/4)				
CIRCLING	1140-1	671 (700-1)	1400-2 3/4	931 (1000-2 3/4)				
			1400-3	931 (1000-3)				

SC-1, 14 MAY 2026 to 11 JUN 2026

SC-1, 14 MAY 2026 to 11 JUN 2026