


LOC/DME I-EPC 109.1 Chan 28	APP CRS 304°	Rwy Ldg 11830 TDZE 10 Apt Elev 13
--	------------------------	--

LDA RWY 26L


DANIEL K INOUE INTL (HNL) (PHNL)

DME required. From CUDEK, NBODY, SHLAE; RNAV 1-GPS required.		MALSF 	MISSED APPROACH: Climb to 600 then climbing left turn to 3000 on HNL VORTAC R-171 to ALANA INT/ HNL 13.9 DME and hold.
	Circling Rwy 22R NA at night. Circling NA to sea lanes 4W, 8W, 22W and 26W. NBODY transition, CUDEK transition, SHLAE transition NA for Cat E aircraft. Follow flasher lights to Rwy 26L. Procedure NA when ALS or SFL inop. Circling Cat E NA. Circling NA for Cats A and B northwest of Rwy 8L-22R. Circling NA for Cats C and D north of Rwy 8L-26R.		

D-ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8 123.9 273.575 (8R/26L)	GND CON 121.9 348.6	CLNC DEL 121.4 281.4
-------------------------------	------------------------------------	---	-------------------------------	--------------------------------



ELEV 13	D	TDZE 10
---------	----------	---------



MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R, and 26R
HIRL Rwy 4R-22L, 8L-26R, and 8R-26L

Procedure NA for arrivals at SAKKI on V16-21 eastbound.

600	3000	ALANA	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 75).		
Use I-EPC DME when on the localizer course.		YUYXE I-EPC 2.2	HEFTL I-EPC 4.4	ONODE I-EPC 5.6	SECIL I-EPC 10.5
		1400	1800	3000	
		2.2 NM	1.3 NM	4.9 NM	
CATEGORY	A	B	C	D	E
S-LDA 26L	600-2 590 (600-2)				
CIRCLING	680-2¼ 667 (700-2¼)	760-2¼ 747 (800-2¼)	820-2¼ 807 (900-2¼)	1400-3 1387 (1400-3)	NA

PAC. 14 MAY 2026 to 09 JUL 2026

PAC. 14 MAY 2026 to 09 JUL 2026