VOR/DME ENA	APP CRS	Rwy Ldg	7575
117.6	012°	TDZE	94
Chan 123		Apt Elev	100

VOR RWY 2L

KENAI MUNI (ENA) (PAEN)

Circling Rwy 2R, 20L NA at night. DME required. When local altimeter setting not received, use Soldotna altimeter setting and increase all MDA 40 feet; increase S-2L Cat C and D visibility ⅛ mile and Circling Cat D visibility ¼ mile. VDP NA with Soldotna altimeter setting. Circling Rwy 2W, 20W NA.

MISSED APPROACH: Climb to 2000 direct ENA VOR/DME and on ENA VOR/DME R-028 to SWANS/ENA 10 DME and hold.

ATIS	ANCHORAGE CENTER	KENAI TOWER★	GND CON	KENAI RADIO
133.35	125.7 379.1	121.3 (CTAF) L 239.3	118.75	122.65

KENAI 117.6 ENA Chan 123

R-028

2200 to DIXIT 192° (10)

223

DOKKA ENA 6

(IAF) ACIGE ENA 20

R-220

(IAF) DIXIT ENA 10

012°

2200 NoPT ENA 20 Arc

237°

057°

2200 012° (10)

(IF) JASGO ENA 20

(IAF) BEYAY ENA 24

R-192

2200 NoPT to JASGO 062° hdg (3.4) and 012° (1.7)

DME REQUIRED

MISSED APCH FIX

028° 208° R-028

SWANS ENA 10

MSA ENA 25 NM

2200 210° 030° 3500

2200 NoPT to JASGO 341° (17.4)

Procedure NA for arrivals at HOM VOR/DME on V438 southbound.

EKAYU

R-341

HOM 20

3500

341° (20)

IAF HOMER 114.6 HOM Chan 93

ELEV 100 D TDZE 94

20W 20R 20L 2W 2R 2L

4600 X 240

7855 X 150

1980 X 75

TWR

012°

REIL Rwy 2L L

HIRL Rwy 2L-20R

Remain within 10 NM

DIXIT ENA 10

192°

012°

2200

2200

DOKKA ENA 6

3.02° TCH 53

900

2000	ENA	ENA R-028	SWANS
		ENA 4.6	ENA 3.6

4 NM 1.4 NM 1.1 NM

CATEGORY	A	B	C	D
S-2L	480-1	386 (400-1)	480-1⅛	386 (400-1⅛)
CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)	580-1½ 480 (500-1½)	680-2 580 (600-2)

AK, 14 MAY 2026 to 09 JUL 2026
AK, 14 MAY 2026 to 09 JUL 2026