LOC/DME I-LER	APP CRS	Rwy Ldg	7100
109.7	340°	TDZE	1232
Chan 34		Apt Elev	1232

ILS or LOC RWY 34

BRAINERD LAKES RGNL (BRD)

RNP APCH - GPS. From GOLLF.

DME required. ADF required.

T NA VDP NA when using AIT altimeter setting. When local altimeter setting not received, use AIT altimeter setting and increase S-ILS 34 DA to 1484 feet; increase all MDAs 60 feet and S-LOC 34 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM.

MALSR

MISSED APPROACH: Climb to 1700 then climbing right turn to 4000 direct LAREW LOM and hold, continue climb-in-hold to 4000.

ASOS	MINNEAPOLIS CENTER	UNICOM
126.775	118.05 239.0	122.7 (CTAF) L



ELEV 1232	TDZE 1232

HIRL Rwys 5-23 and 16-34 L

REIL Rwys 5 and 16 L





CATEGORY	A	B	C	D
S-ILS 34	1432-½ 200 (200-½)			
S-LOC 34	1620-½ 388 (400-½)		1620-⅝ 388 (400-⅝)	
CIRCLING	1760-1 528 (600-1)		1760-1½ 528 (600-1½)	1860-2 628 (700-2)

NC-1, 14 MAY 2026 to 11 JUN 2026
NC-1, 14 MAY 2026 to 11 JUN 2026