

(HSV4.HSV) 24081

AL-5488 (FAA)

HUNTSVILLE INTL-CARL T JONES FLD (HSV)
HUNTSVILLE, ALABAMA

HUNTSVILLE FOUR DEPARTURE

ATIS
121.25
GND CON
121.9 269.525
CLNC DEL
120.35
HUNTSVILLE TOWER ★
127.6 (CTAF) 350.35

**TOP ALTITUDE:
5000**

CUNNINGHAM
113.1 CNG
Chan 78

NASHVILLE
114.1 BNA
Chan 88

WALNUT RIDGE
114.5 ARG
Chan 92

LIVINGSTON
114.35 LVT
Chan 90(Y)

MEMPHIS
117.5 MEM
Chan 122

HINCH MOUNTAIN
117.6 HCH
Chan 123

TAKEOFF MINIMUMS
Rwys 18L/R, 36L/R: Standard.

1600
SHELBYVILLE
113.55 SYI
Chan 82(Y)

NOTE: RADAR required.
NOTE: Use frequency depicted
within the sector where fix/navaid
for your route is located.

HUNTSVILLE
DEP CON WEST ★
118.05 239.0

ROCKET
112.2 RQZ
Chan 59

HUNTSVILLE
DEP CON EAST ★
125.6 354.1

SIDON
114.7 SQS
Chan 94

VULCAN
114.4 VUZ
Chan 91

ROME
115.4 RMG
Chan 101

ALEXANDRIA
116.1 AEX
Chan 108

BIGBEE
116.2 IGB
Chan 109

GADSDEN
112.3 GAD
Chan 70

NOTE: Chart not to scale.

SE-4, 14 MAY 2026 to 11 JUN 2026

SE-4, 14 MAY 2026 to 11 JUN 2026

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 36R: Climb heading 005° to 1600 then on assigned heading for vectors to join filed route. Maintain 5000 or assigned lower altitude. Expect clearance to requested filed altitude/flight level ten minutes after departure.

TAKEOFF ALL OTHER RUNWAYS: Climb on assigned heading for vectors to join filed route. Maintain 5000 or assigned lower altitude. Expect clearance to requested filed altitude/flight level ten minutes after departure.

HUNTSVILLE FOUR DEPARTURE
(HSV4.HSV) 01FEB18

HUNTSVILLE, ALABAMA
HUNTSVILLE INTL-CARL T JONES FLD (HSV)