

WAAS CH 62823 W21A	APP CRS 206°	Rwy Ldg 5502
		TDZE 315
		Apt Elev 315




RNAV (GPS) RWY 21

SIKESTON MEML MUNI (SIK)

RNP APCH.
 ▼ Rwy 21 helicopter visibility reduction below 3/4 SM NA. Baro-VNAV NA when using Cape Girardeau altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Cape Girardeau altimeter setting and increase all DA 49 feet and all MDA 60 feet. Increase LNAV and Circling Cat C/D visibility 1/4 SM.
 ▲ NA

MISSED APPROACH: Climb to 2000 direct CUXID and hold.

AWOS-3PT 119.175	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA	565-1 250 (300-1)			
LNAV/VNAV DA	761-1 3/8 446 (500-1 3/8)			
LNAV MDA	720-1 405 (500-1)		720-1 1/8 405 (500-1 1/8)	
CIRCLING	840-1 525 (600-1)	860-1 545 (600-1)	1080-2 1/4 765 (800-2 1/4)	1160-2 3/4 845 (900-2 3/4)

NC-3, 14 MAY 2026 to 11 JUN 2026

NC-3, 14 MAY 2026 to 11 JUN 2026