ILS Z or LOC Z RWY 4

TALLADEGA MUNI (ASN)

LOC/DME I-ASN	APP CRS	Rwy Ldg	6032
109.95	038°	TDZE	511
Chan 36(Y)		Apt Elev	529

DME required. VDP NA with Anniston altimeter setting. When local altimeter setting not received, use Anniston altimeter setting and increase DA to 744 feet and all MDA 40 feet; increase S-LOC 4 Cat C/D ⅛ mile and Circling Cat C ¼ mile.

MISSED APPROACH: Climb to 1300 then climbing left turn to 3700 on heading 242° and on VUZ VORTAC R-095 to JOTAV INT/VUZ 30 DME and hold.

AWOS-3PT	BIRMINGHAM APP CON	UNICOM
118.425	132.15 285.45	122.8 (CTAF) L

DME REQUIRED



CATEGORY	A	B	C	D
S-ILS 4	711-¾ 200 (200-¾)			
S-LOC 4	1060-1 549 (600-1)		1060-1⅝ 549 (600-1⅝)	
CIRCLING	1140-1 611 (700-1)	1180-1 651 (700-1)	1380-2½ 851 (900-2½)	1500-3 971 (1000-3)

REIL Rwy 4 L
HIRL Rwy 4-22 L

SE-4, 14 MAY 2026 to 11 JUN 2026