

WAAS CH 45905 W22A	APP CRS 215°	Rwy Ldg 7193 TDZE 26 Apt Elev 26
--	------------------------	---

RNAV (GPS) RWY 22


PUNTA GORDA (PGD)

RNP APCH.



⚠ Baro-VNAV NA when using Page Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. When local altimeter setting not received, use Page Fld altimeter setting and increase LPV DA to 276, LNAV/VNAV DA to 360, and all MDAs 60 feet; increase LNAV Cats C and D visibility ¼ SM, and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct BULOW and hold.

ATIS 135,675	FORT MYERS APP CON★ 127.05 306.2	PUNTA GORDA TOWER★ 121.0 (CTAF) 0	GND CON 119.55	UNICOM 122,975
------------------------	--	---	--------------------------	--------------------------



ELEV 26	D	TDZE 26
---------	----------	---------



CATEGORY	A	B	C	D
LPV DA		226-3/4	200 (200-3/4)	
LNAV/VNAV DA		310-1	284 (300-1)	
LNAV MDA	420-1	394 (400-1)	420-1 1/8	394 (400-1 1/8)
CIRCLING	460-1 434 (500-1)	580-1 554 (600-1)	600-1 1/2 574 (600-1 1/2)	740-2 1/4 714 (800-2 1/4)