


LOC/DME I-EYK <b>111.7</b> Chan <b>54</b>	APP CRS <b>048°</b>	Rwy Ldg <b>5500</b> TDZE <b>18</b> Apt Elev <b>19</b>
---	------------------------	---



# ILS or LOC RWY 5

CHESAPEAKE RGNL (CPK)


**⚠** When local altimeter setting not received, use ORF altimeter setting and increase DA to 256 feet; increase all MDAs 40 feet and CEKAD fix minimums S-LOC 5 visibility Cats C and D 1/2 SM. For inop ALS, increase S-LOC 5 Cats C and D visibility to 1 3/8 SM.

**MALSR**  MISSED APPROACH: Climb to 500 then climbing left turn to 2000 on heading 190° and ORF VORTAC R-216 to NALDE INT/I-EYK 12.3 DME and hold.

AWOS-3 <b>123.675</b>	NORFOLK APP CON <b>118.9 353.7</b>	GCO <b>135.075</b>	UNICOM <b>123.075 (CTAF) 0</b>
--------------------------	---------------------------------------	-----------------------	-----------------------------------



CATEGORY	A	B	C	D
S-ILS 5	218-1/2 200 (200-1/2)			
S-LOC 5	480-1/2	462 (500-1/2)	480-1	462 (500-1)
CIRCLING	480-1	461 (500-1)	520-1/2 501 (600-1/2)	580-2 561 (600-2)
CEKAD FIX MINIMUMS				
S-LOC 5	400-1/2	382 (400-1/2)	400-5/8	382 (400-5/8)
CIRCLING	460-1 441 (500-1)	480-1 461 (500-1)	520-1/2 501 (600-1/2)	580-2 561 (600-2)



NE-3, 14 MAY 2026 to 11 JUN 2026

NE-3, 14 MAY 2026 to 11 JUN 2026

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44