

RADAR MINS

26134

N1

RADAR INSTRUMENT APPROACH MINIMUMS

CAMPBELL AAF (FORT CAMPBELL) (KHOP)

Hopkinsville, KY RADAR 1 Amdt 3 RADAR 2 Amdt 4 14MAY26 (26134) (USA)

ELEV 571

RADAR - (E) 134.350x 237.5x 395.9x 258.3x 290.9x

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
ASR ¹	5 ^{2 3 4 5}		AB	980-1	425	(500-1)
			CDE	980-1¼	425	(500-1¼)
	23 ^{2 6 7 8 9}		AB	980/24	409	(500-½)
			CDE	980/40	409	(500-¾)
CIR ¹⁰	5-23		A	1020-1	449	(500-1)
			B	1040-1	469	(500-1)
			C	1040-1½	469	(500-1½)
			DE	1140-2	569	(600-2)
RADAR-2						
PAR ^{11 12}	23 ^{2 6 13 14 15}	3.0°/55/1143	ABCDE	771/24	200	(200-½)
	5 ^{2 3 14 16}	3.0°/50/941	ABCDE	755-¾	200	(200-¾)

¹VGSI and descent angles not coincident.

²Procedure NA when R-3701, R-3702A/B in use.

³Final approach course 045°.

⁴Recommended altitude 4 miles: 1880, 3 miles: 1560, 2 miles: 1240.

⁵FAF 5.0 NM from thld, min alt 2200.

⁶Final approach course 225°.

⁷Recommended altitude 4 miles: 1900, 3 miles: 1580, 2 miles: 1260.

⁸FAF 4.9 NM from thld, min alt 2200.

⁹When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.

¹⁰Circling NA SE of Rwy 5-23.

¹¹PAR unavbl daily 0400-1400Z++.

¹²VGSI and PAR glidepath not coincident.

¹³FAF 4.9 NM from thld.

¹⁴Glide slope intercept altitude 2200.


¹⁵When ALS inop, increase RVR to 40, vis to ¾ mile.

¹⁶FAF 5.0 NM from thld.

SABRE AAF (FORT CAMPBELL) (KEOD)

Clarksville, TN Amdt 4 14MAY26 (26134) (USA)

ELEV 595

RADAR - (E) 118.1 340.9 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
ASR	23 ^{1 2 3 4 5}		COPTER	1040-1	453	(500-1)
	5 ^{1 5 6 7 8 9}		COPTER	1120-1	525	(600-1)

¹FAF 4 NM from THLD, min alt 2200.

²Final approach course 227°.

³Recommended altitude: 3 miles 1800, 2 miles 1400.

⁴KHOP alternate altimeter setting minima 1060-1 473 (500-1).

⁵Use KHOP altimeter when local altimeter not available.

⁶Final approach course 047°.

⁷Recommended altitude: 3 miles 1800, 2 miles 1420.

⁸KHOP alternate altimeter setting minima 1140-1 545 (600-1).

⁹RWY 05 helicopter visibility reduction below ¾ mile not authorized.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26134

N1

SE-1

14 MAY 2026 to 11 JUN 2026

14 MAY 2026 to 11 JUN 2026