

RADAR INSTRUMENT APPROACH MINIMUMS

LEMOORE NAS (REEVES FIELD) (KNLC)

Lemoore, CA Amdt 9 12JUN25 (25163) (USN)

ELEV 228

RADAR - (E) 125.95 270.8x 314.0x 317.575x 322.45x 323.15x 336.4x 346.375x 348.75x 353.55x
363.7x 370.875x 377.075x **▼**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ^{1,2}	32L ^{3,4}	3.0°/40/762	ABCDE	327 - $\frac{1}{4}$	100	(100- $\frac{1}{4}$)
	14L	3.0°/54/1019	ABCDE	319 - $\frac{1}{2}$	100	(100- $\frac{1}{2}$)
	14R ⁵	3.0°/52/998	ABCDE	328 - $\frac{1}{2}$	100	(100- $\frac{1}{2}$)
	32R ⁵	3.0°/46/876	ABCDE	321 - $\frac{1}{2}$	100	(100- $\frac{1}{2}$)
ASR ²	32L ^{6,7}		AB	600 - $\frac{1}{2}$	373	(400- $\frac{1}{2}$)
			CDE	600 - $\frac{5}{8}$	373	(400- $\frac{5}{8}$)
	14L		AB	680 -1	461	(500-1)
			CDE	680 -1 $\frac{3}{8}$	461	(500-1 $\frac{3}{8}$)
	14R ⁵		AB	760 -1	532	(600-1)
			CDE	760 -1 $\frac{1}{2}$	532	(600-1 $\frac{1}{2}$)
32R ⁵		AB	780 -1	559	(600-1)	
		CDE	780 -1 $\frac{5}{8}$	559	(600-1 $\frac{5}{8}$)	
CIR ⁸	14L, 32L		AB	680 -1	452	(500-1)
			C	680 -1 $\frac{1}{2}$	452	(500-1 $\frac{1}{2}$)
			D	780 -2	552	(600-2)
			E	800 -2	572	(600-2)
	14R		AB	760 -1	532	(600-1)
			C	760 -1 $\frac{1}{2}$	532	(600-1 $\frac{1}{2}$)
			D	780 -2	552	(600-2)
			E	800 -2	572	(600-2)
	32R		AB	780 -1	552	(600-1)
			C	780 -1 $\frac{3}{8}$	552	(600-1 $\frac{3}{8}$)
D			780 -2	552	(600-2)	
E			800 -2	572	(600-2)	

14 MAY 2026 to 11 JUN 2026

14 MAY 2026 to 11 JUN 2026

¹No-NOTAM MP: PAR-Rwy 14R-32L 1600-2400Z++ Mon, Rwy 14L-32R 1600-2400Z++ Wed.

²Simultaneous approaches authorized.

³When ALS inop, increase vis to $\frac{1}{2}$ mile.

⁴Caution: WCH 15 ft for group 4 less than required 20 ft.

⁵Pattern at 3000 ft.

⁶When ALS inop, increase vis to 1 mile.

⁷Step Down Fix at 3 NM from thld, 1100 min.

⁸Circling authorized only from ASR.

RADAR INSTRUMENT APPROACH MINIMUMS